









Options for faster lowering and raising





Manual winch w/drill drive adapter

AC and DC power winches available

- Lightweight aerospace grade aluminum construction
- 360 degree rotation
- 3 different boom height adjustments
- Durable powder coat finish
- Truly Portable Design
- One-Person Assembly (No Tools Needed)
- Manual Din rated CE winch with brake (Includes power drill adaptor)
- AC & DC winch options

Weight

Weight (excluding winch)	Boom	Mast	Net
OZA500DAV (lbs)	12	12	24
OZA1000DAV (lbs)	25	22	47

OZA5000DAV shown with optional **OZPED3** Pedestal base and OZGAL.19-50B galvanized wire rope assembly and OZHB10 headache ball

Bases, cable assemblies and headache ball sold separately


WIRE/SYNTHETIC ROPE ASSEMBLIES


(sold separately) Custom length available.


Manual winch: 3/16" - 80 ft max. lift length AC/DC Electric Winch: 3/16" - 90 ft max. lift length

See wire & synthetic rope assembly options on page 3

OZA500DAV DIMENSIONS








OZA500DAV Load Ratings (lbs.)


Based on 3/16" wire rope


	1st. Layer	Mid. Drum	Full Drum
Position 1 (0°)	275	275	275
Position 2 (+22.5°)	330	330	330
Position 3 (+45°)	500	500	500


OZA500DAV BASES (sold separately) Comes with mounting template.


OZPED3 14 88











Dimensions and illustrations are for reference only and subject to change without notice.















sales@ozliftingproducts.com (800) 749-1064





WIRE/SYNTHETIC ROPE ASSEMBLIES

(sold separately) Custom length available.

Manual winch: 1/4" - 55ft max. lift length AC/DC Electric Winch: 1/4" - 45ft max. lift length


See wire & synthetic rope assembly options on page 3


OZA1000DAV Load Ratings (lbs.)


Based on 1/4" wire or 3/16" Ultrex synthetic rope

	1st. Layer	Mid. Drum	Full Drum
Position 1 (0°)	550	550	550
Position 2 (+22.5°)	650	650	550
Position 3 (+45°)	1000	875	550


OZA1000DAV DIMENSIONS









OZA1000DAV BASES (sold separately) Comes with mounting template.







Dimensions and illustrations are for reference only and subject to change without notice.















sales@ozliftingproducts.com (800) 749-1064



OZWB3 shown with OZXR500 OZGAL.19-80B galvanized cable assembly OZHB10 10lbs. headache ball Davit crane, headache ball, and cable assemblies sold separately.

Locking collar included with applicable wheel base kits.

OZWB DAVIT CRANE REACH DIAMETER Sections are representative of hook reach in 360-degrees TELE-PRO 1200 XR SERIES | MIN. 42.00 [1067] MAX. 62.00 [1575] ALUMI-LITE





For all OZ Lifting Products davit cranes up to 1200 lb. capacity

Features

- Industrial strength steel construction with a durable powder-coat finish
- Patented floor-anchoring system allows the davit to rotate while under load (when base is not anchored the davit must remain in a forward position when lifting)
- Features two fixed casters and two swivel casters with locking brakes to make moving the base and davit crane easy
- Forklift pockets (for transporting only)
- Made in USA

Davit crane sold separately

Patent Pending Floor-Anchoring System



OZWB OZWB1 **OZWB1-TP**


Wheel Base for all OZ davit cranes up to 1200 lb. capacity (Pedestal Base not included) Wheel Base with Pedestal Base for use with OZ1200DAV


OZWB2 **OZWB2-TP**

Wheel Base with Pedestal Base for use with OZ1000DAV, OZCF1200DAV Wheel Base with Pedestal Base for use with OZXR500DAV, OZ500DAV, OZA500DAV Wheel Base with Pedestal Base for use with OZTP1000DAV, OZXR1000DAV, OZA1000DAV

OZWB3 Wheel Base with Pedestal Base for use with OZTP500DAV

OZWB DIMENSIONS








ADJUSTABLE LEG EXTENSIONS

POSITION 1 38.06 [967]

FLOOR-ANCHORING SYSTEM

















Dimensions and illustrations are for reference only and subject to change without notice.



WIRE/SYNTHETIC ROPE ASSEMBLIES

Steel Wire Rope (For manual winch)		
OZGAL.19-80B	3/16" x 80'	Galvanized cable assembly
OZSS.19-80B	3/16" x 80'	Stainless steel cable assembly
OZGAL.25-55B	1/4" x 55'	Galvanized cable assembly
OZSS.25-55B	1/4" x 55'	Stainless steel cable assembly

Above cable assemblies come with swaged ball and swivel hook with latch. **Custom cable length available.**

3/16" - 80 ft. max. length • 1/4" - 55 ft. max. length

Steel Wire Rope (For manual and power winch)		
OZGAL.19-90	3/16" x 90'	Galvanized cable assembly
OZSS.19-90	3/16" x 90'	Stainless Steel cable assembly
OZGAL.25-45	1/4" x 45'	Galvanized cable assembly
OZSS.25-45	1/4" x 45'	Stainless Steel cable assembly

All cable assemblies come with a swivel hook with latch.

Custom cable length available.

3/16" - 90 ft. max. length • 1/4" - 45 ft. max. length



Synthetic Rope		
OZSR.19-15	3/16"x 15'	Ultrex Synthetic Rope
OZSR.19-50	3/16"x 50'	Ultrex Synthetic Rope
OZSR.19-90	3/16"x 90'	Ultrex Synthetic Rope
OZSR.25-50	1/4" x 50'	Ultrex Synthetic Rope
OZSR.25-75	1/4" x 75'	Ultrex Synthetic Rope
OZSR.31-45	5/16" x 45'	Ultrex Synthetic Rope

All synthetic rope assemblies come with looped ends and pre-installed swivel hook with latch










HEADACHE BALL

OZHB10

Keeps your wire rope tensioned even when lowering the hook with no load. Compatible with 3/16" and 1/4" wire rope assemblies. Headache balls sold separately from all davit cranes and wire rope assemblies.



davit cranes 1200 lbs. capacity or less excluding the XR series.



Store and transport your davit crane in this davit crane roller bag. Fits OZ Lifting Products davit crane models OZ500DAV, OZ1000DAV, OZA500DAV, & OZA1000DAV.



















sales@ozliftingproducts.com (800) 749-1064