WIRELESS ADAPTERS

The OZ Lifting Products Wireless Adapter is a plug-and-play unit that allows the user the ability to control their OZ Electric Chain Hoist or OZ Electric Builder's Hoist wirelessly from up to 250 feet away. The Wireless Adapter can be installed in minutes and connects to the hoist to improve safety, productivity, and efficiency for a variety of lifting applications.

ELECTRIC

Features

- Operate the hoist from a safe distance of up to 250 feet while keeping line of sight
- Compact and lightweight design easily connects and pairs to OZ Electric Chain Hoist or OZ Electric Builder's Hoist
- Improved safety, productivity, and efficiency
- 115V receiver voltage

Standards - CE, FCC

Wireless adapter kits include: Transmitter, receiver, mounting bracket, and hardware. Remote requires (2) AA batteries - not included. Hoist sold separately.

BUILDER'S HOIST	OBHWA-T500	OBHWA-T1000	OBHWA
Dimensions (Length x Width x Height)	6 X 4 X 5	8 X 5 X 7	10 X 4.5 X 3.5
Weight Assembled (lb)	1.2 lb.	1.8 lb.	2.6 lb.
Receiver Voltage	115 V	115 V	115 V
Transmitter Battery	AA (x2)	AA (x2)	AA (x2)
Operating Range (Line of Sight)	250 ft.	250 ft.	250 ft.
Wireless Adapter Compatibility	Wireless Adapter for use with: OBH500 (Only models with serial numbers starting with "T" and "KW")	Wireless Adapter for use with: OBH1000 (Only models with serial numbers starting with "T" and "KW")	Wireless Adapter for use with: OBH500 & OBH1000 (Only serial numbers starting with "K", "KR", and "500") Plug & Play
ELECTRIC CHAIN HOIST (ECWA)			
Dimensions (Length x Width x Height)	7 X 12 X 4.5		
Weight Assembled (lb.)	3.4 lb.		
Receiver Voltage	115 V		
Transmitter Battery	AA (x2)		
Operating Range (Line of Sight)	250 ft.		
Wireless Adapter Compatibility	OZ1000EC (All serial numbers), OZ2000EC (Excluding serial numbers starting with "V"), OZ4000EC (Excluding serial numbers starting with "V")		





























OBH500 shown

Dimensions and illustrations are for reference only and subject to change without notice.

